

TRACTOR PACKAGE



FULLY LOADED PACKAGE - WE SOURCE LOW HOUR VERMEERS TO GET YOU UP AND RUNNING QUICKLY

SAW 16F attached to a low hour Vermeer RTX550. The price is variable depending on the base price of the used machine. A clean RTX550 with less than 1000 hours mated with a new SAW 16F microtrench saw is \$120k. Lead time is approximately 2-3 weeks, but may be less. Quoted price does not include shipping.

Full Saw Attachment Saw16-F

This 16" deep cut saw attachment will adapt to almost any hydrostatic tractor such as the Vermeer RTX550 or Ditch Witch* RT80. This attachment has side shift, plunge cut. 4" or 6" vacuum transitions. 30-40 GPM attachment flow is recommended.



Blades

AR (Abrasion Resistant) Plate is used for all components, it is twice the strength of the steel used by our competitors. Our blades cut faster and cleaner than others on the market and last longer as well.



OUR RECOMMENDED TRACTOR - VERMEER RTX550

Experience dependable performance and versatility with the **RTX550**, a low hour, pre serviced, pre inspected used machine built to deliver results day after day. Designed for reliability and ease of operation, the RTX550 combines efficient power with a durable build, making it ideal for both demanding tasks and everyday use. With its proven track record and excellent maintenance history, this model offers exceptional value for anyone seeking performance without compromise. Get the strength, stability, and confidence you need—at a fraction of the cost of new.



GENERAL DIMENSIONS AND WEIGHTS

Weight (basic tractor, rubber tires): 5600 lbs (2540.1 kg)
Length (basic tractor, rubber tires): 10.3 " (26.2 cm)
Width (basic tractor, rubber tires): 72.4 " (183.9 cm)
Height (basic tractor, rubber tires): 96.8 " (245.9 cm)

ENGINE DETAILS

Make and Model: Cummins B3.3
Manufacturer's gross hp rating: 65 hp (48.5 kw)
Maximum Torque: 158 ft-lb (214.2 Nm)
Number of Cylinders: 4
Cooling Medium: Liquid
Maximum Operating Angle (Fore/Aft)*: 35 deg
Maximum Operating Angle (Left/Right)*: 35 deg
Fuel Type: Diesel
Emissions rating: Tier 4i (EI Stage IIIA)
Guaranteed sound power (CE-rating): 108 dB(A)
Noise Level at Operator's Ear: 90 dB(A)

CAPACITIES

Fuel Tank: 27 gal (102.2 L)
Hydraulic Tank: 18 gal (68.1 L)
Hydraulic System: 20 gal (75.7 L)
Coolant: 3 gal (11.4 L)


HYDRAULIC SYSTEM

Ground drive pump capacity: 31 gpm (117.3 L/min)
Ground drive pump relief: 4350 psi (299.9 bar)
Attachment pump capacity: 31 gpm (117.3 L/min)
Attachment pump relief: 5080 psi (350.3 bar)
Auxiliary pump capacity: 11.6 gpm (43.9 L/min)
Auxiliary pump relief: 2500 psi (172.4 bar)

SAW16

Specifications

Weight: 560 lbs (254 kg)
Length: 102 " (259.08 cm)
Wheel Diameter: 43.1" (109.5 cm)
Minimum Cutting Width: .750 " (1.9 cm)
Maximum Cutting Width: 2.50 " (6.35 cm)
Maximum Cutting Depth: 16" (40.6 cm)



Interested in our other Saws?
Have a look at our comparison table here

